de Heus- XCMG
Stougjesdijk 153 3271 KB
Mijnsheerenland NL
info@heustractors.com
+31 (0) 186 61 2333

XCMG XE80E

Fitted as standard with:

- Kubota Stage-V diesel engine (54.6 kW)
- Proportional hydraulic system with 1 variable pump
- Demolition/sorting function (auxiliary flow with high yield)
- Steel tracks (450 mm wide)
- Swivelling boom (62° left / 50° right)
- Dozer blade with float function
- Safety cab with ROPS/OPG certification
- NVH-optimised silent cab
- 0.35 m³ excavator bucket (earthworks version)
- Boom 3.4 m and arm 1.82 m
- Counterweight 1200 kg
- Hydraulic tank 130 litres, diesel tank 130 litres

€87,840.00

Specifications

DIMENSIONS

Boom length	3400
Cabin width	2300
Chassis width	2300
Counterweight free space	818.5
Cradle base	2272
Ground clearance	386
Height of dozer blade	495 mm
Height of tracks	698
Height to top of roof	3220
Max cutting depth of dozer blade	307
Max. Digging depth	4254
Max. Digging height	8325
Max. Tipping height	6440
Max. Vertical digging depth	3300
Max. excavation radius	7890
Maximum lifting height of dozer blade	3095
Maximum reach at GRP	7710
Min. forcing radius	3945
Minimum unloading height	6440
Overall length with bin	6220
Overall width	2300
Platform width	2975
Tail swing radius	1545
Track length	2900
Track width	1850
Width of tracks	450
Width of upper structure	2250

ENGINE

Cooling	Liquid
Rated speed	2200

HYDRAULIC SYSTEM	
Driving system pressure	235
Main pressure safety valve	283
Main pump output	229
Steering pressure	37
Swing system pressure	235

OTHER	
Diesel tank	130
Engine oil capacity	13
Hydro tank	130

TECHNICAL SPECIFICATIONS	
Arm digging force	41
Ground pressure	42.3
Max traction force	64
Max. Digging force	64
Rotation speed	12

WEIGHT	
Own weight	9500

Pictures

XE80E

XCMG
XE80E

XCMG
XE80E

XCMG

CAUTION