de Heus- XCMG
Stougjesdijk 153 3271 KB
Mijnsheerenland NL
info@heustractors.com
+31 (0) 186 61 2333

XCMG XE160WE

Fitted as standard with:

- Cummins B4.5 Stage V diesel engine
- 115 kW (154 hp) power
- Stage V emission standard
- Hydrostatic four-wheel drive
- Kawasaki hydraulic system
- Proportional joystick controls
- 8-inch colour display
- Two travel modes: working mode & transport mode
- Maximum travel speed: 20 km/h
- Dozer blade and hydraulically adjustable outriggers
- 360° swivel range
- Slew rate: 9 rpm
- Rear and side cameras
- OPG cab (safety cab)
- Fully adjustable air-suspension seat
- Integrated air conditioning
- LED front & rear working lights
- Quick-change system for attachments
- AUX1 & AUX2 hydraulic connections
- Maximum flow rate AUX1 & AUX2: 120 L/min

€0.00

Specifications

DIMENSIONS

Cabin width	2490
Counterweight free space	1262
Cradle base	2550
Ground clearance	424
Height to top of roof	3195
Max. Digging depth	4385
Max. Digging height	9626
Max. Tipping height	7163
Max. Vertical digging depth	3373
Max. excavation radius	8752
Min. forcing radius	3089
Overall length with bin	8085
Overall width	2550
Platform width	2550
Track width	1943

ENGINE

Cooling	Liquid
Rated speed	2000

HYDRAULIC SYSTEM

Driving system pressure	370
Main pressure safety valve	370
Main pump output	160
Steering pressure	39
Swing system pressure	250

OTHER

Diesel tank	250
Engine oil capacity	8
Hydro tank	118

TECHNICAL SPECIFICATIONS	
Arm digging force	86
Ground pressure	48.9
Max traction force	97
Max. Digging force	120
Rotation speed	11.5

WEIGHT	
Own weight	15880

Pictures

XE160WE