



de Heus- XCMG
Stougjesdijk 153 3271 KB
Mijnsheerenland NL
info@heustractors.com
+31 (0) 186 61 2333



XCMG XE55E

Fitted as standard with:

- Kubota Stage-V
- Hammer function
- Proportional demolition/sorting function
- Air-conditioned
- Dozer-Blade
- Rubber tracks

€54,720.00

Specifications

DIMENSIONS

Cabin width	1960
Counterweight free space	637
Cradle base	1990
Ground clearance	315
Height of tracks	550
Height to top of roof	2555
Max. Digging depth	3640
Max. Digging height	5650
Max. Tipping height	4010
Max. Vertical digging depth	2690
Max. excavation radius	6110
Min. forcing radius	1040
Overall length with bin	5340
Overall width	1960
Platform width	1830
Width of tracks	400

ENGINE

Cooling	Liquid
Rated speed	2200

HYDRAULIC SYSTEM

Driving system pressure	300
Main pressure safety valve	300
Main pump output	158.4
Steering pressure	35
Swing system pressure	240

OTHER

Diesel tank	68
Engine oil capacity	9.5
Hydro tank	46

TECHNICAL SPECIFICATIONS

Arm digging force	24.3
Ground pressure	32
Max traction force	52.8
Max. Digging force	44.4
Rotation speed	9.5

WEIGHT

Own weight	5700
------------	------

Pictures

