**de Heus- XCMG**
Stougjesdijk 153 3271 KB
Mijnsheerenland NL
info@heustractors.com
+31 (0) 186 61 2333

# XCMG XC7-SR07E

Fitted as standard with:

- Electric drive with 80V LFP battery (35 kWh)
- 2 travel motors of 8.5 kW each + 15 kW working hydraulic motor
- Proportional hydraulic system with 3rd function (79 l/min, 21 MPa)
- Fully enclosed safety cabin
- Electrodynamic braking system + emergency stop button in cabin
- Standard 0.45 m³ bucket (1800 mm wide)
- Maximum tipping angle 101° and dumping range 550 mm
- Clearance height 1960 mm - working height up to 3800 mm
- Load capacity 910 kg - tipping load 1820 kg
- Swing circle over tyres: 1640 mm
- DC fast charging up to 16 kW (charging time ±2.2 hours)

**€0.00**

## Specifications

## DIMENSIONS

| | |
|---|---|
| Bin capacity | 0.45 |
| Cradle base | 1079 |
| Ejection height | 2400 |
| Ground clearance | 185 |
| Height to top of roof | 1960 |
| Loading height | 2400 |
| Maximum angle on ground | 32 |
| Overall length with bin | 3410 |
| Overall length without bin | 2703 |
| Overall width | 1640 |
| Range (m) | 550 |
| Storage angle at max. height | 40 |
| Tilting angle at max. lifting height | 101 |
| Tipping angle | 22 |
| Total working height | 3800 |
| Track width | 1370 |
| Tray width | 1800 |
| Turning circle | 1792 |

## ELECTRIC MOTOR

| | |
|---|---|
| Driving motor | 8.5 |
| Running time | 6 - 8 uur |

## HYDRAULIC SYSTEM

| | |
|---|---|
| Oil yield | 79 |
| Workload | 210 bar |

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| Max. Digging force | 21.5 |
| Total cycle time | 11 |

## WEIGHT

| | |
|---|---|
| Own weight | 3150 |

## Pictures

XCMG
XC7-SR07

XCMG
XC7-SR07

XCMG
XC7-SR07

XCMG
XC7-SR07

XCMG
XC7-SR07

XCMG
XC7-SR07

XCMG
XC7-SR07

XCMG
XC7-SR07

System settings

STANDARD FLOW

STANDARD FLOW

20.0

XCMG